Pipeline Services



CHT1675 Hot Tapping machine 66" stroke – Ø3 - 16" capacity



A Hot Tapping machine with a working pressure capacity of 5000 p.s.i maximum and can Hot tap from Ø3 – 16" specifically designed for all pipeline intervention and wellhead maintenance.

- Helical geared drive.
- Drive as close to cutter as possible
- Internally pressure balanced system
- Auto variable feed gearbox and motor
- Geared mechanical depth display
- Constant seal & pressure monitoring


Technical Details

RANGE			
Minimum tapping hole diameter	76mm	3″	
Maximum tapping hole diameter	405mm	16″	
Maximum design operating pressure	5000 p.s.i	345 bar	
Mirage certified operating pressure	1480 p.s.i	100 bar	
Maximum operating temperature	200° C	392° F	
Spindle bar travel	1675mm	66″	
Spindle bar minimum clearance	75mm	3″	
R.P.M	Min: 5	Max: 40	
Drive – Pneumatic	4.0 Hp	3.0 Kw	
Drive – Hydraulic	5.0 Hp	3.7 Kw	
Feed – Pneumatic	1.5 Hp	1.11 Kw	
Feed – Hydraulic	2.2 Hp	1.64 Kw	
Air Consumption / supply required	98 s.c.f.m	2.69 m3/m	
Hydraulic supply required @ 1050 p.s.i	50 L/min	13 gal/min	

FEED RATES		
Feed rate – Manual / revolution	10mm	0.393″
Feed rate auto feed	0 - 8mm/min	0315″/min

WEIGHTS AND DIMENSIONS			
449 kgs	988 lbs		
580 Kgs	1276 lbs		
	449 kgs		

Shipping dimensions	L - 308cm - (121")	W- 66cm (26")	H- 79cm (31")
-	2655		



The machine is supplied complete with Hot tap machine, feed and drive motor, lifting brackets, (3-4"), (6-12") (12–16") cutter holders, connection hoses and pressure gauge, Toolkit, air filter lubricator (when required), all required mounting studs and nuts and connection spool, storage / shipping box, CE certificate, Packing list and Manual – pressure certification 1480 psi (100 bar)

Pishgam Sanat Abzar Co.

200

.60

Main office: No 372, 3rd floor, Abzar & Yaragh center, Imam Khomeini Street, Tehran, Iran Tel. +982166712530, +982166713540

Manufacturing site: No. 3, 15 th St., Rezvanieh, Kamalshahr, Karaj, Iran. Tel.; +982634717900-4 info@pishgam.co.ir, www.pishgam.co.ir



Optional Accessories

HTC3 - HTC36 Standard hot tap cutters from 3 - 36"	HYPP60-30-3ph 15 Hp tandem hydraulic power pack 60 lpm @ 70 bar – 380/440v 3 phase HYPP60-D 15Hp hydraulic power pack 60 lpm @ 70 bar – diesel engine
SHTPD3 – SHTPD36 Standard hot tap pilot drills with wire retainers	CHT-5000PT Third party pressure test with calibrated test equipment
LSC4 – LSC36 Line stop cutters 4 – 36"	LSPD4 –LSPD36 Standard line stop pilot drills with wire retainers
150-3FA - 600-24FA Standard flange adapters (3 - 24") #150, #300, #600	SPECIAL FLANGE ADAPTERS Special flange adapters (3 – 24") #900, #2500, PN16, API and line stop
HTC3EX – HTC36EX Extended hot tap cutters from 3 – 36"	SHTPD3EX – SHTPD36EX Extended hot tap pilot drills 3 – 36″
LSFH4 – LSFH36 Line stop folding heads 4 – 24"	LSA2-6 – LSA6- 12 – LSA12-24 Line stop actuator machines (manual and hydraulic)

Pishgam Sanat Abzar Co.

Main office: No 372, 3rd floor, Abzar & Yaragh center, Imam Khomeini Street, Tehran, Iran Tel. +982166712530, +982166713540

Manufacturing site: No. 3, 15 th St., Rezvanieh, Kamalshahr, Karaj, Iran. Tel.; +982634717900-4 info@pishgam.co.ir, www.pishgam.co.ir

