

CHT815 Hot Tapping machine

32" stroke - Ø2 - 10" capacity



A Hot Tapping machine with a working pressure capacity of 5000 p.s.i maximum and can Hot tap from $\emptyset 2 - 10''$ specifically designed for all pipeline intervention and wellhead maintenance.

- Helical geared drive.
- Drive as close to cutter as possible
- Internally pressure balanced system
- Auto variable feed gearbox and motor
- Geared mechanical depth display
- Constant seal & pressure monitoring


Technical Details


RANGE		
Minimum tapping hole diameter	51mm	2″
Maximum tapping hole diameter	254mm	10"
Maximum design operating pressure	350 bar	5000 p.s.i
Standard certified pressure	102 bar	1480 p.s.i
Maximum operating temperature	200° C	392° F
Spindle bar travel	813mm	32"
Spindle bar minimum clearance	51mm	2"
R.P.M	Min: 5	Max: 40
Drive – Pneumatic	4.0 Hp	3.0 Kw
Drive – Hydraulic	5.0 Hp	3.7 Kw
Feed – Pneumatic	1.5 Hp	1.11 Kw
Feed – Hydraulic	2.2 Hp	1.64 Kw
Air Consumption / supply required	98 s.c.f.m	2.69 m3/m
Hydraulic supply required @ 1050 p.s.i	50 L/min	13 gal/min

FEED RAT	ES	
Feed rate - Manual / revolution	10mm	0.393"
Feed rate auto feed	0 - 8mm/min	0315"/min

WEIGHTS AND DI	MENSIONS	
Machine weight including connection spool	300 kgs	660lbs
Shipping weight	475 Kgs	1045 lbs

Shipping dimensions L - 222cm - (87") W- 63cm (25") H- 70cm





The machine is supplied complete with Hot tap machine, feed and drive motor, lifting brackets, (3-4"), (6-12") cutter holders, connection hoses and pressure gauge, Toolkit, air filter lubricator (when required), all required mounting studs and nuts and connection spool, storage / shipping box, CE certificate, Packing list and Manual – pressure certification 1480 psi (100 bar)

Pishgam Sanat Abzar Co.



Main office: No 372, 3rd floor, Abzar & Yaragh center, Imam Khomeini Street, Tehran, Iran Tel. +982166712530, +982166713540

Optional Accessories



HTC3 – HTC36 Standard hot tap cutters from 3 – 36"



HYPP60-30-3ph 15 Hp tandem hydraulic power pack 60 lpm @ 70 bar - 380/440v 3 phase HYPP60-D 15Hp hydraulic power pack 60 lpm @ 70 bar -

diesel engine



SHTPD3 – SHTPD36Standard hot tap pilot drills with wire retainers



CHT-5000PT Third party pressure test with calibrated test equipment



LSC4 – LSC36 Line stop cutters 4 – 36"



LSPD4 -LSPD36 Standard line stop pilot drills with wire retainers



150-3FA - 600-24FA Standard flange adapters (3 - 24") #150, #300, #600



SPECIAL FLANGE ADAPTERS Special flange adapters (3 – 24") #900, #2500, PN16, API and line stop



HTC3EX – HTC36EX Extended hot tap cutters from 3 – 36"



SHTPD3EX –
SHTPD36EX Extended hot tap pilot drills 3 – 36"



LSFH4 – LSFH36 Line stop folding heads 4 – 24"



LSA2-6 - LSA6-12 - LSA12-24 Line stop actuator machines (manual and hydraulic)

Pishgam Sanat Abzar Co.

